



Okoguard®-Okolon® TS-CPE Type MV-105 15kV Shielded Power Cable

One Okopact® (Compact Stranded) Copper Conductor/105°C Rating
100% and 133% Insulation Level

For Cable Tray Use-Sunlight Resistant



- A Uncoated, Okopact (Compact Stranded) Copper Conductor
- B Strand Screen-Extruded Semiconducting EPR
- C Insulation-Okoguard EPR
- D Insulation Screen-Extruded Semiconducting EPR
- E Shield Copper Tape
- F Jacket-Okolon TS-CPE

Insulation

Okoguard is Okonite's registered trade name for its exclusive ethylene-propylene (EPR) based, thermosetting compound, whose optimum balance of electrical and physical properties is unequaled in other solid dielectrics. Okoguard insulation, with the distinctive red color and a totally integrated EPR system, provides the optimum balance of electrical and physical properties for long, problem free service. The triple tandem extrusion of the screens with the insulation provides optimum electrical characteristics.

Jacket

The Okolon TS-CPE jacket on this cable is a vulcanized chlorinated polyethylene base compound which is mechanically rugged, flame, radiation, and oil resistant.

Applications

Okoguard shielded Okolon TS-CPE Type MV-105 power cables are recommended for use as feeder circuits in electric utility generating stations, for distribution circuits, and for feeders or branch circuits in industrial and commercial installations. Type MV cables may be installed in wet or dry locations, indoors or outdoors (exposed to sunlight), in any raceway or underground duct, directly buried if installed in a system with a grounding conductor in close proximity that conforms with NEC Section 250.4(A)(5), or messenger supported in industrial establishments and electric utilities. Sizes 1/0 AWG and larger may also be installed in cable tray.

Specifications

Conductor: Annealed uncoated copper compact stranded per ASTM B-496.

Strand Screen: Extruded semiconducting EPR strand screen. Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, CSA C68.10 and UL 1072.

Insulation: Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, CSA C68.10 and UL 1072.

Insulation Screen: Extruded semiconducting EPR insulation screen. Meets or exceeds

electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, CSA C68.10 and UL 1072.

Shield: 5 mil bare copper tape helically applied, with 25% minimum overlap.

Jacket: Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, CSA C68.10 and UL 1072 for chlorinated polyethylene jackets.

UL listed as Type MV-105, sunlight resistant and for use in cable tray in accordance with UL 1072.

CSA C68.10 listed as FT4, SR, and LTDD (-25°C).

Product Features

- Triple tandem extruded, all EPR system.
- Okoguard cables meet or exceed all recognized industry standards (UL, AEIC, NEMA/ICEA, IEEE).
- 105°C continuous operating temperature.
- 140°C emergency rating.
- 250°C short circuit rating.
- Passes UL and IEEE 383 and 1202 (1/0 AWG & larger) Vertical Tray Flame Tests.
- Excellent corona resistance.
- Screens are clean stripping.
- Exceptional resistance to "treeing."
- Moisture resistant.
- Resistant to most oils, acids, and alkalis.
- Sunlight resistant.
- For Cable Tray Use; 1/0 AWG and larger.
- Improved Temperature Rating.

Okoguard-Okolon TS-CPE Type MV-105

15kV Shielded Power Cable

One Okopact (Compact Stranded)

Copper Conductor/ 105°C Rating

100% and 133% Insulation Level

For Cable Tray Use-Sunlight Resistant

Product Data Section 2: Sheet 11



| Catalog Number (1) | Conductor Size AWG or kcmil | | Conductor Size - mm ² | | Approx. Dia. over Insulation (in.) | | Approx. Dia. over Screen (in.) | | Jacket Thickness - mils | | Approx. O.D. - mm | | Approx. O.D. - Inches | | Approx. Net Weight (lbs./1000') | | Approx. Ship Weight (lbs./1000') | | Ampacities (2) Conduit in Air | | Ampacities (3) Underground | | Ampacities (4) Cable Tray | | Conduit (5) Size Inches* | |
|--------------------|--------------------------------|--|----------------------------------|--|---------------------------------------|--|-----------------------------------|--|----------------------------|--|-------------------|--|-----------------------|--|------------------------------------|--|-------------------------------------|--|----------------------------------|--|-------------------------------|--|------------------------------|--|-----------------------------|--|
|--------------------|--------------------------------|--|----------------------------------|--|---------------------------------------|--|-----------------------------------|--|----------------------------|--|-------------------|--|-----------------------|--|------------------------------------|--|-------------------------------------|--|----------------------------------|--|-------------------------------|--|------------------------------|--|-----------------------------|--|

Okoguard Insulation: 175 mils (4.45mm), 100% Insulation Level

| | | | | | | | | | | | | | | |
|-------------|------|-------|------|------|----|------|------|------|------|------|-----|-----|-----|----|
| 115-23-2011 | 2 | 33.6 | 0.67 | 0.73 | 60 | 1.52 | 0.89 | 22.5 | 585 | 640 | 165 | 165 | — | 3 |
| 115-23-2013 | 1 | 42.4 | 0.70 | 0.76 | 80 | 2.03 | 0.96 | 24.4 | 700 | 765 | 190 | 185 | — | 3 |
| 115-23-2015 | 1/0 | 53.5 | 0.73 | 0.79 | 80 | 2.03 | 1.00 | 25.3 | 790 | 855 | 215 | 215 | 220 | 3 |
| 115-23-2017 | 2/0 | 67.4 | 0.77 | 0.83 | 80 | 2.03 | 1.04 | 26.4 | 905 | 965 | 255 | 245 | 250 | 3 |
| 115-23-2019 | 3/0 | 85.0 | 0.82 | 0.88 | 80 | 2.03 | 1.09 | 27.6 | 1040 | 1110 | 290 | 275 | 290 | 3 |
| 115-23-2021 | 4/0 | 107.0 | 0.87 | 0.93 | 80 | 2.03 | 1.13 | 28.7 | 1200 | 1280 | 330 | 315 | 335 | 3½ |
| 115-23-2023 | 250 | 127.0 | 0.93 | 0.99 | 80 | 2.03 | 1.19 | 30.3 | 1370 | 1450 | 365 | 345 | 370 | 3½ |
| 115-23-2027 | 350 | 177.0 | 1.01 | 1.07 | 80 | 2.03 | 1.28 | 32.4 | 1725 | 1825 | 440 | 415 | 460 | 4 |
| 115-23-2031 | 500 | 253.0 | 1.13 | 1.19 | 80 | 2.03 | 1.39 | 35.4 | 2255 | 2370 | 535 | 500 | 575 | 4 |
| 115-23-2035 | 750 | 380.0 | 1.31 | 1.37 | 80 | 2.03 | 1.57 | 39.9 | 3140 | 3320 | 655 | 610 | 745 | 5 |
| 115-23-2038 | 1000 | 507.0 | 1.46 | 1.52 | 80 | 2.03 | 1.73 | 43.9 | 4020 | 4255 | 755 | 690 | 890 | 5 |

Okoguard Insulation: 220 mils (5.59mm), 133% Insulation Level

| | | | | | | | | | | | | | | |
|---------------|------|-------|------|------|-----|------|------|------|------|------|-----|-----|------|----|
| 115-23-2111 | 2 | 33.6 | 0.75 | 0.81 | 80 | 2.03 | 1.01 | 25.8 | 710 | 775 | 165 | 165 | — | 3 |
| 115-23-2113 | 1 | 42.4 | 0.79 | 0.85 | 80 | 2.03 | 1.05 | 26.7 | 790 | 860 | 190 | 185 | — | 3 |
| 115-23-2115 | 1/0 | 53.5 | 0.82 | 0.88 | 80 | 2.03 | 1.08 | 27.5 | 880 | 945 | 215 | 215 | 220 | 3½ |
| 115-23-2117 | 2/0 | 67.4 | 0.86 | 0.92 | 80 | 2.03 | 1.12 | 28.5 | 995 | 1075 | 255 | 245 | 250 | 3½ |
| 115-23-2119 | 3/0 | 85.0 | 0.91 | 0.97 | 80 | 2.03 | 1.18 | 29.9 | 1145 | 1225 | 290 | 275 | 290 | 3½ |
| 115-23-2121 | 4/0 | 107.0 | 0.96 | 1.02 | 80 | 2.03 | 1.22 | 31.1 | 1310 | 1400 | 330 | 315 | 335 | 3½ |
| 115-23-2123 | 250 | 127.0 | 1.01 | 1.07 | 80 | 2.03 | 1.28 | 32.4 | 1465 | 1565 | 365 | 345 | 370 | 4 |
| 115-23-2127 | 350 | 177.0 | 1.10 | 1.16 | 80 | 2.03 | 1.37 | 34.7 | 1840 | 1940 | 440 | 415 | 460 | 4 |
| ▲ 115-23-2131 | 500 | 253.0 | 1.22 | 1.28 | 80 | 2.03 | 1.49 | 37.7 | 2385 | 2570 | 535 | 500 | 575 | 5 |
| ▲ 115-23-2135 | 750 | 380.0 | 1.40 | 1.46 | 80 | 2.03 | 1.66 | 42.2 | 3285 | 3540 | 655 | 610 | 745 | 5 |
| 115-23-2138 | 1000 | 507.0 | 1.54 | 1.60 | 110 | 2.79 | 1.87 | 47.5 | 4275 | 4540 | 755 | 690 | 890 | 6 |
| 115-23-2144 | 1250 | 633.5 | 1.75 | 1.81 | 110 | 4.33 | 2.08 | 52.7 | 5255 | 5645 | 845 | 770 | 995 | 6 |
| 115-23-2145 | 1500 | 760.2 | 1.88 | 1.94 | 110 | 4.33 | 2.20 | 56.0 | 6140 | 6540 | 925 | 845 | 1090 | 8 |

Okonite's web site, www.okonite.com contains the most up to date information.

▲ **Authorized Stock Item.** Available from our Customer Service Centers.

Aluminum Conductors

(1) Aluminum conductors are available on special order.

Ampacities

(2) Ampacities are in accordance with Table 310.60(C)(73) of the NEC for three single Type MV-105 conductors, or single conductors twisted together (triplexed) and installed in an isolated conduit in air at an ambient temperature of 40°C and a conductor temperature of 105°C.

(3) Ampacities are in accordance with Table 310.60(C)(77) of the NEC for three single conductors or triplexed cable in one underground raceway, three feet deep with a conductor temperature of 105°C, 100% Load Factor, an ambient earth temperature of 20°C and thermal resistance (RHO) of 90.

(4) Ampacities based on single Type MV-105 conductors, or single conductors twisted together (triplexed, quadruplexed, etc.), size 1/0 AWG and larger, installed in uncovered cable tray in accordance with Section 392.80(B) of the NEC at an ambient temperature of 40°C and a conductor temperature rating of

105°C. In accordance with NEC Section 392.80(B)(2)(a), the ampacities are 75% of the values given in NEC Table 310.60(C)(69) (copper conductors). Where the cable tray is covered for more than six feet with solid unventilated covers, the ampacities shall not exceed 93% of the values shown above.

Refer to the NEC, IEEE/ICEA-S-135 Power Cable Ampacities, or the Okonite Engineering Data Bulletin for installation in duct banks, multiple point grounded shields, other ambient temperatures, circuit configurations or installation requirements.

(5) Recommended size of rigid or nonmetallic conduit for three conductors based on 40% maximum fill.

*The jam ratio conduit I.D. to cable O.D. should be checked to avoid possible jamming.

 **THE OKONITE COMPANY**
Ramsey, New Jersey 07446