




X-Olene® Type XHHW-2

600V Power and Control

Copper Conductor/90°C Wet or Dry



A Bare, Solid or Stranded
Copper Conductor
B X-Olene Insulation

Insulation

X-Olene is Okonite's trade name for its chemically cross-linked polyethylene insulating compound with outstanding electrical and physical properties. Its excellent chemical physical resistance permits X-Olene's use in areas exposed to alcohol, ketones and dilute acids and bases, without additional coverings.

Applications

X-Olene Type XHHW-2 600 Volt Cables are recommended for general low voltage power and control applications. Where the National Electrical Code applies, Type XHHW-2 may be used up to 90°C in wet or dry locations. These cables may be installed in wet or dry locations, indoors or outdoors, in raceways, underground ducts, or lashed to a messenger for aerial installation.

Specifications

Conductor: Uncoated soft copper per ASTM B-3. Solid per ASTM B-3. Sizes smaller than #8 are compress stranded per ASTM B-8. Sizes #8 and larger are compact stranded per ASTM B-496..

Insulation: Meets or exceeds all requirements of ICEA S-95-658, NEMA WC-70, and UL Standards.

Listed by Underwriters Laboratories, Inc. as Type XHHW-2.

Product Features

- Small diameter, permits use of smaller conduit or more wires per conduit.
- Excellent heat resistance.
- Rated 90°C in dry or wet locations.
- Mechanically rugged.
- Stable electrical properties.
- Low moisture absorption.
- Highly resistant to weather and most chemicals.
- UL Listed.

X-Olene Type XHHW-2

600V Power and Control

Copper Conductor/90°C Wet or Dry



Product Data

Section 3: Sheet 3

Catalog Number	Conductor Size AWG or kcmil		Number of Strands	Insulation Thickness - mils		Approx. O.D. - Inches		Approx. Net Weight lbs./1000'		Approx. Ship Weight lbs./1000'		90°C Wet (1) NEC Ampacity	75°C Wet (1) NEC Ampacity	ICEA Ampacity (2)
112-31-3061	14	1	30	0.76	0.13	3.30	17	22	15	15	24			
• 112-31-3071	14	7	30	0.76	0.14	3.56	18	23	15	15	24			
112-31-3101	12	1	30	0.76	0.15	3.81	25	30	20	20	30			
• 112-31-3111	12	7	30	0.76	0.15	3.81	26	31	20	20	30			
112-31-3141	10	1	30	0.76	0.17	4.32	37	42	30	30	42			
• 112-31-3151	10	7	30	0.76	0.18	4.57	39	44	30	30	42			
112-31-3221	8	1	45	1.14	0.23	5.84	62	67	55	50	55			
• 112-31-3231	8	7	45	1.14	0.23	5.84	62	67	55	50	55			
• 112-31-3271	6	7	45	1.14	0.27	6.89	94	99	75	65	75			
• 112-31-3311	4	7	45	1.14	0.31	7.87	144	155	95	85	97			
• 112-31-3371	2	7	45	1.14	0.37	9.40	223	246	130	115	130			
112-31-3401	1	19	55	1.40	0.42	10.7	282	305	150	130	156			
• 112-31-3421	1/0	19	55	1.40	0.46	11.7	352	384	170	150	179			
• 112-31-3441	2/0	19	55	1.40	0.50	12.7	439	471	195	175	204			
112-31-3461	3/0	19	55	1.40	0.54	13.7	548	580	225	200	242			
• 112-31-3481	4/0	19	55	1.40	0.60	15.2	685	724	260	230	278			
• 112-31-3511	250	37	65	1.65	0.66	16.8	814	853	290	255	317			
• 112-31-3541	350	37	65	1.65	0.76	19.3	1126	1181	350	310	384			
• 112-31-3581	500	37	65	1.65	0.87	22.1	1591	1655	430	380	477			
112-31-3641	750	61	80	2.03	1.07	27.2	2385	2485	535	475	598			
112-31-3701	1000	61	80	2.03	1.22	31.0	3159	3275	615	545	689			

• component stock available for faster delivery.

View Okonite's web site, www.okonite.com, for the most up to date dimensions.

To order a color other than black, change the last digit of the catalog number as follows:			
White	2	Orange	5
Red	3	Blue	6
Green	4	Yellow	7
Example: To order #14/SOL - Red, the catalog number would be 112-31-3063.			

Ampacities

(1) Ampacities are based on Table 310-16 of the National Electrical Code for these 90°C rated conductors at an ambient temperature of 30°C. The 75°C wet column is provided for additional information.

The ampacities shown apply to open runs of cable, installation in any approved raceway, direct burial in the earth, or as aerial cable on a messenger. Derating for more than three current carrying conductors within a raceway is in accordance with NEC Section 310.15.B.2.

(2) Based on three (3) conductors in a single enclosed or exposed conduit. Capacities based on 40°C air ambient using ICEA methods. For 30°C ambient multiply values by 1.10; for 50°C multiply by .90. For other ambients or installation conditions refer to Okonite's Engineering Data Book EHB.