



Okonite® Okolon TS - CPE® Duplex Case Wire

600V

One Copper Conductor/90°C Rating



- A Stranded Uncoated Copper Conductor
- B Insulation—Okonite, #10 AWG, 2/64"
- C Jacket—Okolon TS-CPE

Insulation

Okonite EPR is Okonite's trade name for its heat resistant, mechanically rugged ethylene-propylene based insulating compound. The insulation thickness is 2/64".

Jackets and Finishes

The Okolon TS-CPE thermoset chlorinated polyethylene jacket supplied with this cable provides excellent resistance to mechanical abuse, flame, weathering and most acids, oils and alkalis. Color Codes: 1-Black, 1-Black with tracer.

Applications

Okonite Okolon TS-CPE 600V Case Wire is recommended for use as relay and associated signal apparatus wiring and for connector wire use where a flexible, small diameter wire is required.

Specifications

Conductor: Uncoated stranded copper per ASTM B-38.
Insulation: Per ICEA S-95-658.
Jacket: Per ICEA S-95-658, Part 4.1.13.

Product Features

- Exceptional heat resistance.
- 90°C Continuous Rating
130°C Emergency Overload Rating.
250°C Short Circuit Rating.
- Mechanically rugged.
- Flexible, easy to handle and splice.
- Flame resistant — meets U.L. horizontal flame test.
- Resistant to most oils, acids, alkalis and effects of weather.
- Stable electrical and physical properties.

Okonite Insulation: 2/64"

Catalog Number	Size AWG	No. of Strands	Jacket Thickness 64 th's	Approx. Duplexed O.D. (In.)	Approx. Net Wt. Lbs./M'	Approx. Ship Wt. Lbs./M'
▲151-12-1702	10	19	1	.43	98	120

▲ **Authorized Stock Item** - Available from Customer Service Centers.
Standard Package — 500' spool.

D/13030714



THE OKONITE COMPANY

Ramsey, New Jersey 07446